



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.09.2019

Version number 1

Revision: 23.09.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking· **1.1 Product identifier**· **Trade name:** PHOSPHORESCENT PAINT NIGHTGLOW - SPRAYCAN· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

· **Application of the substance / the preparation :** Coating compound/ Surface coating/ paint· **1.3 Details of the supplier of the safety data sheet**· **Manufacturer/Supplier:**

STARDUSTCOLORS

ZA DE TESAN PLAN SUD – 30126 ST LAURENT DES ARBRES

– France TEL 0033 4.66.50.61.66

Email : info@stardustcolors.com<https://www.stardustcolors.co.uk>· **1.4 Emergency telephone number:**

France (INRS 24h/24) - Tel : +33 (0)1 45 42 59 59

Ireland - Tel : 00 353 1 8092568 - 00 353 1 8379964 (24h/24) EU Tel: 112

Belgique - Tel : 32 070/245 245

UK : Call NHS 999 in a medical emergency. If you urgently need medical help or advice but it's not a life-threatening situation, call 111 (24/7). The NHS 111 number is currently only available in certain areas. If you're outside of these areas, you should call NHS Direct on 0845 4647

SECTION 2: Hazards identification· **2.1 Classification of the substance or mixture**· **Classification according to Regulation (EC) No 1272/2008 :**

GHS02

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

· **2.2 Label elements**· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**

GHS02

· **Signal word** Danger· **Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

· **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

· **Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

(Contd. on page 2)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.09.2019

Version number 1

Revision: 23.09.2019

Trade name: PHOSPHORESCENT PAINT NIGHTGLOW - SPRAYCAN

(Contd. of page 1)

- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**
- **Description:** Mixture: consisting of the following components.

Dangerous components:

CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 RTECS: TX 2275000 Reg.nr.: 01-2119486944-21	propane ⚠ Flam. Gas 1, H220; Press. Gas (Comp.), H280	25-50%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 RTECS: EJ 4200000 Reg.nr.: 01-2119474691-32	butane ⚠ Flam. Gas 1, H220; Press. Gas (Comp.), H280	10-25%
CAS: 110-19-0 EINECS: 203-745-1 Index number: 607-026-00-7 Reg.nr.: 01-2119488971-22	isobutyl acetate ⚠ Flam. Liq. 2, H225	10-25%
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 RTECS: AL 3150000 Reg.nr.: 01-2119471330-49-xxxx	acetone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	2.5-<10%
CAS: 1330-20-7 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32-xxxx	xylene ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	2.5-<10%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226	<2.5%
CAS: 1344-28-1 EINECS: 215-691-6 RTECS: BD 1200000 Reg.nr.: 17-2119921087-41-xxxx	aluminium oxide	<2.5%

· **SVHC** No· **Additional information:** For the wording of the listed risk phrases, refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **After inhalation:** Provide fresh air; consult a doctor in case of medical complaints.

(Contd. on page 3)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.09.2019

Version number 1

Revision: 23.09.2019

Trade name: PHOSPHORESCENT PAINT NIGHTGLOW - SPRAYCAN

(Contd. of page 2)

- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** Do not induce vomiting; call for medical help immediately.
- **4.2 Most important symptoms and effects, both acute and delayed :**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed :**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture :** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures :**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow the product to enter sewers/ surface water or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections :**
See Section 7 for information on safe handling.
See Section 8 for information on personal protective equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling :**
Keep receptacles tightly sealed.
Keep away from heat and direct sunlight.
Open and handle receptacle with care.
- **Information about fire - and explosion protection:**
Do not spray onto a naked flame or any incandescent material.



Keep ignition sources away - Do not smoke.

Protect from heat.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

(Contd. on page 4)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.09.2019

Version number 1

Revision: 23.09.2019

Trade name: PHOSPHORESCENT PAINT NIGHTGLOW - SPRAYCAN

(Contd. of page 3)

- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility: Not required.**
- **Further information about storage conditions:**
Keep container tightly sealed.
Do not seal receptacle gas tight.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
- **7.3 Specific end use(s) : No further relevant information available.**

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities: No further data; see section 7.**
- **8.1 Control parameters**

Ingredients with limit values that require monitoring at the workplace:

CAS: 74-98-6 propane (25-50%)

MAK (Switzerland)	Short-term value: 7200 mg/m ³ , 4000 ppm Long-term value: 1800 mg/m ³ , 1000 ppm
-------------------	---

CAS: 106-97-8 butane (10-25%)

WEL (Great Britain)	Short-term value: 1810 mg/m ³ , 750 ppm Long-term value: 1450 mg/m ³ , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
MAK (Switzerland)	Short-term value: 7600 mg/m ³ , 3200 ppm Long-term value: 1900 mg/m ³ , 800 ppm

CAS: 110-19-0 isobutyl acetate (10-25%)

WEL (Great Britain)	Short-term value: 903 mg/m ³ , 187 ppm Long-term value: 724 mg/m ³ , 150 ppm
MAK (Switzerland)	Short-term value: 960 mg/m ³ , 200 ppm Long-term value: 480 mg/m ³ , 100 ppm SSc;

CAS: 67-64-1 acetone (<5%)

WEL (Great Britain)	Short-term value: 3620 mg/m ³ , 1500 ppm Long-term value: 1210 mg/m ³ , 500 ppm
IOELV (EU)	Long-term value: 1210 mg/m ³ , 500 ppm
MAK (Switzerland)	Short-term value: 2400 mg/m ³ , 1000 ppm Long-term value: 1200 mg/m ³ , 500 ppm B;

CAS: 1330-20-7 xylene (<5%)

WEL (Great Britain)	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
IOELV (EU)	Short-term value: 442 mg/m ³ , 100 ppm Long-term value: 221 mg/m ³ , 50 ppm Skin

(Contd. on page 5)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.09.2019

Version number 1

Revision: 23.09.2019

Trade name: PHOSPHORESCENT PAINT NIGHTGLOW - SPRAYCAN

(Contd. of page 4)

<i>MAK (Switzerland)</i>	Short-term value: 870 mg/m ³ , 200 ppm Long-term value: 435 mg/m ³ , 100 ppm H B;
CAS: 108-65-6 2-methoxy-1-methylethyl acetate (≤2.5%)	
<i>WEL (Great Britain)</i>	Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm Sk
<i>IOELV (EU)</i>	Short-term value: 550 mg/m ³ , 100 ppm Long-term value: 275 mg/m ³ , 50 ppm Skin
<i>MAK (Switzerland)</i>	Short-term value: 275 mg/m ³ , 50 ppm Long-term value: 275 mg/m ³ , 50 ppm SSc;

· DNELs

CAS: 67-64-1 acetone

<i>Oral</i>	<i>DNEL Public long-term systemic</i>	62 mg/kg bw/d
<i>Dermal</i>	<i>DNEL Public long-term systemic</i>	62 mg/kg bw/d
	<i>DNEL Worker long-term systemic</i>	186 mg/kg bw/d
<i>Inhalative</i>	<i>DNEL Public long-term systemic</i>	200 mg/m ³
	<i>DNEL Worker long-term systemic</i>	1,210 mg/m ³
	<i>DNEL Worker long-term local effects</i>	2,420 mg/m ³
	<i>DNEL Worker acute/short-term local effects</i>	2,420 mg/m ³

CAS: 1330-20-7 xylene

<i>Inhalative</i>	<i>DNEL Worker acute/short-term local effects</i>	289 mg/m ³
-------------------	---	-----------------------

· PNECs

CAS: 67-64-1 acetone

<i>PNEC STP</i>	100 mg/L
<i>PNEC aqua (fresh water)</i>	10.6 mg/L
<i>PNEC aqua (intermittent releases)</i>	21 mg/L
<i>PNEC aqua (marine water)</i>	1.06 mg/L
<i>PNEC sediment (fresh water)</i>	30.4 mg/kg
<i>PNEC sediment (marine water)</i>	3.04 mg/kg
<i>PNEC soil</i>	29.5 mg/kg

CAS: 1330-20-7 xylene

<i>PNEC STP</i>	6.58 mg/L
<i>PNEC aqua (fresh water)</i>	0.327 mg/L
<i>PNEC aqua (intermittent releases)</i>	0.327 mg/L
<i>PNEC aqua (marine water)</i>	0.327 mg/L
<i>PNEC sediment (fresh water)</i>	12.46 mg/kg
<i>PNEC sediment (marine water)</i>	12.46 mg/kg
<i>PNEC soil</i>	2.31 mg/kg

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.09.2019

Version number 1

Revision: 23.09.2019

Trade name: PHOSPHORESCENT PAINT NIGHTGLOW - SPRAYCAN

(Contd. of page 5)

· Ingredients with biological limit values:

CAS: 67-64-1 acetone (<5%)

BAT (Switzerland)	80 mg/l Medium: U Sampling time: b Parameter: Aceton
-------------------	---

CAS: 1330-20-7 xylene (<5%)

BMGV (Great Britain)	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
BAT (Switzerland)	2 g/l Medium: U Sampling time: b Parameter: Methylhippursäuren

· Additional information:

The most current valid lists have been used as a basis for the production of this document.

· 8.2 Exposure controls

· Personal protective equipment:

· General protective and hygienic measures: Wash hands before breaks and at the end of work.

· Respiratory protection:

Not required.

Use suitable respiratory protective device in case of insufficient ventilation.

· Protection of hands:



Protective gloves

· Gloves material : Nitrile rubber, NBR

· Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Aerosol
Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.

· pH-value: Not determined.

(Contd. on page 7)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.09.2019

Version number 1

Revision: 23.09.2019

Trade name: PHOSPHORESCENT PAINT NIGHTGLOW - SPRAYCAN

(Contd. of page 6)

· Change in condition Melting point/freezing point: Undetermined. Initial boiling point and boiling range: 55.8-56.6 °C
· Flash point: -97 °C
· Flammability (solid, gas): Not applicable.
· Ignition temperature: 365 °C
· Decomposition temperature: Not determined.
· Auto-ignition temperature: Product is not self igniting.
· Explosive properties: Not determined.
· Explosion limits: Lower: 1.5 Vol % Upper: 10.9 Vol %
· Vapour pressure at 20 °C: 8,300 hPa
· Density at 20 °C: <1 g/cm ³ · Relative density : Not determined. · Vapour density : Not determined. · Evaporation rate : Not applicable.
· Solubility in / Miscibility with water: Not miscible or difficult to mix.
· Segregation coefficient (n-octanol/water): Not determined.
· Viscosity: Dynamic: Not determined. Kinematic: Not determined.
· Solvent content: COV (CH) : 79.50 % · 9.2 Other information : No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions :** No dangerous reactions known.
- **10.4 Conditions to avoid :** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

(Contd. on page 8)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.09.2019

Version number 1

Revision: 23.09.2019

Trade name: PHOSPHORESCENT PAINT NIGHTGLOW - SPRAYCAN

(Contd. of page 7)

· LD/LC50 values relevant for classification:**CAS: 110-19-0 isobutyl acetate**

Oral	LD50	13,400 mg/kg (rat)
------	------	--------------------

CAS: 67-64-1 acetone

Oral	LD50	5,800 mg/kg (rat)
Dermal	LD50	20,000 mg/kg (rabbit)

CAS: 1330-20-7 xylene

Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
Inhalative	LC50/4 h	11 mg/l (ATE)

CAS: 1344-28-1 aluminium oxide

Oral	LD50	>5,000 mg/kg (rat)
------	------	--------------------

CAS: 108-65-6 2-methoxy-1-methylethyl acetate

Oral	LD50	8,532 mg/kg (rat)
Inhalative	LC50/4 h	35.7 mg/l (rat)

· Primary irritant effect:

- **On the skin:** Based on available data, the classification criteria are not met.
- **On the eyes:** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitization** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information**· 12.1 Toxicity****· Aquatic toxicity:****CAS: 67-64-1 acetone**

LC50 96h	4,740-6,330 mg/l (fish)
EC50 48h	21.6-23.9 mg/l (Crustaceans)

CAS: 1330-20-7 xylene

LC50 96h	7,711-9,591 mg/l (fish)
----------	-------------------------

CAS: 1344-28-1 aluminium oxide

LC50 48h	14.6 mg/l (fish)
EC50 48h	38.2 mg/l (daphnia)

- **12.2 Persistence and degradability :** No further relevant information available.
- **12.3 Bioaccumulative potential :** No further relevant information available.
- **12.4 Mobility in soil :** No further relevant information available.

(Contd. on page 9)

GB



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.09.2019

Version number 1

Revision: 23.09.2019

Trade name: PHOSPHORESCENT PAINT NIGHTGLOW - SPRAYCAN

(Contd. of page 8)

- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water



Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects :** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation :**



Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- **European waste catalogue**

HP3	Flammable
-----	-----------

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN-Number**
- **ADR, IMDG, IATA** UN1950
- **14.2 UN proper shipping name**
- **ADR** UN1950 AEROSOLS
- **IMDG** AEROSOLS
- **IATA** AEROSOLS, flammable

- **14.3 Transport hazard class(es)**

- **ADR**



- **Class** 2 5F Gases.

(Contd. on page 10)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.09.2019

Version number 1

Revision: 23.09.2019

Trade name: PHOSPHORESCENT PAINT NIGHTGLOW - SPRAYCAN

(Contd. of page 9)

· Label	2.1
· IMDG, IATA	
	
· Class	2.1
· Label	2.1
· 14.4 Packing group	
· ADR, IMDG, IATA	Not classified as hazardous for transport
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user	Warning: Gases.
· Danger code (Kemler):	-
· EMS Number:	F-D,S-U
· Stowage Code	SW1 Protected from sources of heat. SW2 Clear of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t

(Contd. on page 11)

GB



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.09.2019

Version number 1

Revision: 23.09.2019

Trade name: PHOSPHORESCENT PAINT NIGHTGLOW - SPRAYCAN

(Contd. of page 10)

- **Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t**
- **REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3**
- **15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.**

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.

· **Classification according to Regulation (EC) No 1272/2008**

Aerosols	Bridging principles
----------	---------------------

· **Abbreviations and acronyms:**

- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOCV: Lenkungsabgabe auf flüchtigen organischen Verbindungen, Schweiz (Swiss Ordinance on volatile organic compounds)
- DNEL: Derived No-Effect Level (REACH)
- PNEC: Predicted No-Effect Concentration (REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- SVHC: Substances of Very High Concern
- vPvB: very Persistent and very Bioaccumulative
- Flam. Gas 1: Flammable gases – Category 1
- Aerosol 1: Aerosols – Category 1
- Press. Gas (Comp.): Gases under pressure – Compressed gas
- Flam. Liq. 2: Flammable liquids – Category 2
- Flam. Liq. 3: Flammable liquids – Category 3
- Acute Tox. 4: Acute toxicity – Category 4
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
- Asp. Tox. 1: Aspiration hazard – Category 1